

Einfach
besser!

MicroCAFS PBK®
patented mixing technology

MC6SP10 BP BA

Tragbare Geräte für Profis

Löschgerät

Durchfluss:	11 l/min. (nass) 5.4 l/min. (trocken)
Einsatzzeit:	60 sek. (nass) 122 sek. (trocken)
Reichweite:	11.5 m (nass) 8 m (trocken)
Behältergröße:	11 l
Arbeitsdruck:	ca. 8 bar
Treibgas:	6 l / 300 bar Druckluft
Temperatur:	0°C - 60°C
Gewicht:	15.5 kg leer, 27 kg gefüllt
Abmessungen:	670 x 460 x 300 mm (HxBxT)
Löschmittel:	zugelassene Schaummittel
Rating EN3:	bis zu 43 A 233 B (löschmittelabhängig)
elektr. Anlagen:	Sicherheitsabstände beachten

Atemschutzgerät

Modell:	Dräger PAS Colt
Druckluftflasche:	3 l / 300 bar Composite
Lungenautomat:	Dräger PSS ESA
Atemanschluss:	Dräger Panorama Nova ESA

Stand 05/2015, Änderungen vorbehalten

Ihr Händler:



www.microcafs.de

MicroCAFS PBK GmbH ■ Burgwaldring 4 ■ 86697 Oberhausen

Simply
better!

MicroCAFS PBK®
patented mixing technology

MC6SP10 BP BA

Portable for professionals

Extinguisher


Flow rate:	11 l/min. (wet) 5.4 l/min. (dry)
Operating time:	60 sec. (wet) 122 sec. (dry)
Work range:	11.5 m (wet) 8 m (dry)
Vessel capacity:	11 l
Operating pressure:	approx. 8 bar
Propellant:	3 l / 300 bar compressed air
Temperature:	0°C - 60°C
Weight:	15.5 kg empty, 27 kg filled
Size:	670 x 460 x 300 mm (HxWxD)
Extinguishing agent:	approved foam agent
Rating EN3:	Up to 43 A 233 B (depending of foam agent)
Electric area:	consider safety distance

Breathing apparatus

Model:	Dräger PAS Colt
Air cylinder:	3 l / 300 bar Composite
Regulator:	Dräger PSS ESA
Breathing mask:	Dräger Panorama Nova ESA

Status 05-2015, subject to modifications

Your distributor:



www.microcafs.com

MicroCAFS PBK GmbH ■ Burgwaldring 4 ■ 86697 Oberhausen ■ Germany