

Einfach  
besser!

**MicroCAFS<sup>®</sup> PBK<sup>®</sup>**  
patented mixing technology

## **MC6SP10**

### **Tragbare Geräte für Profis**

Durchfluss:	11 l/min. (nass) 5.4 l/min. (trocken)
Einsatzzeit:	55 sek. (nass) 115 sek. (trocken)
Reichweite:	11.5 m (nass) 8 m (trocken)
Behältergröße:	10.4 l
Arbeitsdruck:	ca. 8 bar
Treibgas:	2 l / 300 bar Druckluft
Temperatur:	0°C - 60°C
Gewicht:	12.5 kg leer, 22.5 kg gefüllt
Abmessungen:	625 x 300 x 220 mm (HxBxT)
Löschmittel:	zugelassene Schaummittel
Rating EN3:	bis zu 43 A 233 B (löschmittelabhängig)
elektr. Anlagen:	Sicherheitsabstände beachten

Stand 05/2015, Änderungen vorbehalten

**Ihr Händler:**



[www.microcafs.de](http://www.microcafs.de)

MicroCAFS PBK GmbH ■ Burgwaldring 4 ■ 86697 Oberhausen

Simply  
better!

**MicroCAFS<sup>®</sup> PBK<sup>®</sup>**  
patented mixing technology


## **MC6SP10**

### **Portable for professionals**

Flow rate:	11 l/min. (wet) 5.4 l/min. (dry)
Operating time:	55 sec. (wet) 115 sec. (dry)
Work range:	11.5 m (wet) 8 m (dry)
Vessel capacity:	10.4 l
Operating pressure:	approx. 8 bar
Propellant:	2 l / 300 bar compressed air
Temperature:	0°C - 60°C
Weight:	12.5 kg empty, 22.5 kg filled
Size:	625 x 300 x 220 mm (HxWxD)
Extinguishing agent:	approved foam agent
Rating EN3:	up to 43 A 233 B (depending of foam agent)
Electric area:	consider safety distance

Status 05-2015, subject to modifications

### **Your distributor:**



[www.microcafs.com](http://www.microcafs.com)

MicroCAFS PBK GmbH ■ Burgwaldring 4 ■ 86697 Oberhausen ■ Germany